

LTN7608-P8 8 Channel Professional Level IP NVR

Platinum 3 year warranty
Features

- Simultaneous HDMI and VGA output
- H.264 Compression Technology
- Intuitive Graphic User Interface
- Quick Search, Easy Backup
- Remote Monitoring / Control via NVMS or Web Browsers
- Multi-User management
- Live View on Smart Phones and Playback on iPhones
- 3 Year Warranty & Free Life-Time Technical Support



Specifications

System	Compression Format	H.264	
	OS	Embedded Linux	
	IP Input	8CH, Max 40Mbps Input	
	VGA Output	1 CH Resolution: 1920×1080P/60Hz, 1600×1200/60Hz, 1280×1024/60Hz, 1280×720/60Hz, 1024×768/60Hz	
	CVBS	-	
	HDMI Output	1 CH Resolution: 1920×1080P/60Hz, 1600×1200/60Hz, 1280×1024/60Hz, 1280×720/60Hz, 1024×768/60Hz	
	Video / Audio Out	Recording Resolution	5MP / 3MP / 2MP / 1080P / 720P / D1 / VGA / DCIF / 2CIF / CIF / QCIF
		Simultaneous Playback	8-ch, 4CIF (Real-time) 8-ch, 4-ch 720P, 2-ch 1080P, 5 MP (No Realtime)
		Playback Resolution	5MP / 3MP / 2MP / 1080P / 720P / D1 / VGA / DCIF / 2CIF / CIF / QCIF
		Dual Stream	Main and Sub-Streams
	Audio Input	1CH RCA	
	Audio Output	1CH RCA	
	Backup Format	MP4	
Storage	SATA	2 SATA Interfaces for 2 HDDs	
	eSATA	-	
	Capacity	up to 4TB Capacity per Hard Drive	
External Interface	Network Interface	1 RJ45 10M/100M/1000M adaptive Ethernet 8 independent 10/100 Mbps PoE Ethernet	
	USB Interface	2x USB 2.0	
	Serial Interface	1xRS-485	
	Alarm Input	-	
	Alarm Output	-	
Built-in POE	Standard	802.3af standard	
	Power Consumption	120W total	
	Mobile App	NVMS7000 for iPhone/iPad/Android	
	Consumption	≤ 15 W (without hard disk)	
General	Power Supply	100VAC ~ 240VAC	
	Operating Temperature	-10°C ~55°C	
	Humidity	10% ~ 90% Humidity	
	Chassis	19-inch rack-mounted 1U chassis	
	Dimension	17.5" × 11.4" ×1.8" (W x D x H)	
	Weight	≤ 2 Kg (without hard disk)	

Front/Back View

