



1 PORT INJECTOR

Midspan

10/100Mbps

Data transfer speed

19W MAX POWER

DC 48V

IEEE 802.3af

PoE standard

SLIDE-IN DESIGN

Connect multiple devices

SAFETY PROTECTION

For low power devices

No. of PoE Ports	1
Pass Through Data Rates	10/100 Mbps
Standards	IEEE 802.3af
Switch Type	Internal, Unmanaged
Switching Method	Store & Forward
Filtering/Forwarding Rates	100Mbps port - 148,800pps 10Mbps port - 14,880pps
Transmission Media	10BaseT Cat. 3, 4, 5 UTP/STP 100BaseTX Cat. 5 UTP/STP
Output Power Voltage	48 VDC Maximum/350 mA
User Port Power	19 Watts Maximum
AC Input Voltage	100 ~ 240 VAC
AC Input Current	0.8A @ 100-240 VAC
AC Frequency	50 to 60 Hz
PoE Output Pin Configuration	Mode-B 4/5(+), 7/8(-)
Dimensions	5.75" x 2.5" x 1.75"
Weight	.35 lbs
Indicators	System Indicator: AC Power (Green)
Connectors	RJ-45
Operating Temperature	14 °F to 113 °F
Regulatory	RoHS Compliant, CE/FCC
Safety Approvals	EN 60950:2006