



LTPOE-SW2402A

24 Port + 2 Port GE Switch
Upto 1000 Mbps | 250W | 802.3at/af



24 POE PORTS

Plus 2 Port GE Switch + DIP Switch

Upto 1000Mbps

Data transfer rate

250W MAX POWER

Max 30W per port

IEEE 802.3at/af

Standard

POWER PROTECTION

On low powered devices

UNMANAGED

Ports automatically detect devices

Standard

IEEE 802.3/u 10/100/1000BaseT/TX
IEEE 802.3x Flow Control
IEEE 802.3at/af POE compliant midspan
PoE compliant

Number of PoE Ports

24 PoE Ports + 2 Port GE Switch

MAC Address Table

8K

Buffer Memory

512KB

Transmission Method

Store and Forward

Filtering/Forwarding Rates

1000Mbps Port - 1,488,000pps
100Mbps Port - 148,800pps
10Mbps Port - 14,880pps

Transmission Media

10BaseT Cat 3, 4, 5 UTP
1000/100BaseTX Cat. 5 UTP/SFP

Output PoE Pin

4, 5, 7, 8

LED Indicators

Port 1~24: 10/100M, PoE ON?OFF Power,
Port 25, 26: 10/100/1000M

Power Input

100-240VAC, 50~60Hz

Power Output

56VDC 3.6A (250W)

Power Consumption

250W Max Power, 30W per Port

Dimensions / Weight

480 x 118 x 40 mm (L x W x H)

Operating Temperature

0°C to 40°C

Humidity

10 to 90% RH (non-condensing)

Certifications

FCC Class A, CE