

## CMHT2322-28F

### Platinum 2 MP 4-in-1 Turret Camera



#### Key Features

- 2 MP high performance CMOS sensor
- 2.8 mm fixed lens
- 2D DNR
- 4-in-1 video output (switchable among TVI / AHD / CVI / CVBS)
- IP66

## Specifications

<b>Camera</b>	
Imaging Device	1/3" Progressive CMOS
Min. Illumination	0.05 lux @ F1.2 (AGC on); 0 Lux with IR on
Video Output	BNC
Resolution	2 MP: 1920 (H) × 1080 (V)
Max. Framerate	AHD / TVI / CVI: P/ @ 25fps, N/ @ 30 fps CVBS: 960 H
Focal Length (Zoom Ratio)	2.8 mm
Max. Aperture Ratio	F2.0
Angular Field of View	Hor: 91.84°, Vert: 50.04°, Diag: 107.73°
Min. Object Distance	0.6 m
Lens Type	Fixed lens
<b>Menu</b>	
IR Range	Up to 66 ft (20 m)
On Screen Display	English
Day & Night	Ext / Color / B/W
Backlight Compensation	Off / User BLC
Digital Noise Reduction	2D DNR
Gain Control	Auto
White Balance	ATW
Electronic Shutter Speed	Auto
Reverse	Mirror
Remote control interface	ACP (AHD Coax Protocol)
Video Transmission Distance	Max. 300 m (Cable: 5C 2V)
<b>General</b>	
Operating Temperature / Humidity	-22° to 122° F (-30° to 50° C), Humidity: 90% or less (non-condensation)
Ingress Protection	IP66
Input Voltage / Current	12 VDC
Power Consumption	IR on: 3.5 W, IR off : 0.5 W
Color / Material	Metal
Dimensions	Φ 3.94 × 3.54 in. (Φ 100 × 90 mm)
Weight	approx. 30.82 lbs (70 g)

## Dimensions

