


PTZIP424W-X25IR Platinum 4 MP 25 × Network IR PTZ Camera



The PTZIP424W-X25IR 4 MP Network IR PTZ Camera utilizes a 1/2.8" progressive scan CMOS chip. With the 25x optical zoom lens, the camera offers more details over expansive areas. This series of cameras can be used for a wide range of high-definition applications, such as the rivers, forests, roads, railways, airports, ports, squares, parks, scenic spots, stations, large venues, etc.

- High quality imaging with 4 MP resolution, up to 30 fps
- Excellent low-light performance via Ultra-Low Light technology
- Clear imaging against strong back lighting thanks to 120 dB WDR technology
- Pan and tilt maneuverability enables the camera to monitor zones of interest
- 25x optical zoom allows for closer viewing of subjects in expansive areas
- Up to 164 ft (50 m) IR range ensures safety at night
- Water and dust resistance (IP66)
- Human and vehicle target classification

Detection, Observation, Recognition, Identification (DORI)

The DORI distance gives users a general idea of the camera's ability to distinguish persons or objects within its field of view. It is calculated using the camera sensor specification and the criteria given by EN 62676-4: 2015.

DORI	Detect	Observe	Recognize	Identify
Definition	25 px/m	63 px/m	125 px/m	250 px/m
Distance (Tele)	7,217.8 ft (2,200 m)	2,864.2 ft (873 m)	1,443.6 ft (440 m)	721.8 ft (220 m)


Specifications

Camera	
Image Sensor	1/2.8" Progressive Scan CMOS
Max. Resolution	2560 × 1440
Min. Illumination	Color: 0.005 Lux @ (F1.6, AGC on), B/W: 0.001 Lux @ (F1.6, AGC on), 0 Lux with IR
Shutter Speed	1/1 to 1/30,000 sec.
Day & Night	IR cut filter
Zoom	25x optical, 16x digital
Slow Shutter	Yes
Lens	
Focal Length	4.8 to 120 mm
Field of View	Horizontal 53.3° to 2.6°, vertical 30.6° to 1.5°, diagonal 60.5° to 3°
Focus	Auto, semi-auto, manual
Aperture	Max. F1.6
Zoom Speed	Approx. 3.4 s
Illuminator	
Supplemental Light Type	IR
Supplemental Light Range	IR Distance: up to 164 ft (50 m)
Smart Supplemental Lighting	Yes
IR Wavelength	850 nm
Functionality	
Movement Range (Pan)	0° to 360°
Movement Range (Tilt)	-5° to 90°
Pan Speed	Pan speed: Configurable from 0.1° to 300°/sec.; preset speed: 350°/sec.
Tilt Speed	Tilt speed: Configurable from 0.1° to 160°/sec. preset speed 200°/sec.
Proportional Zoom	Yes
Presets	300
Preset Freezing	Yes
Patrol Scan	8 patrols, up to 32 presets for each patrol
Pattern Scan	4 pattern scans, record time over 10 minutes for each scan
Park Action	Preset, pattern scan, patrol scan, auto scan, tilt scan, random scan, frame scan, panorama scan
3D Positioning	Yes
PTZ Status Display	Yes
Scheduled Task	Preset, pattern scan, patrol scan, auto scan, tilt scan, random scan, frame scan, panorama scan, dome reboot, dome adjust

Power-off Memory	Yes
Video	
Main Stream	60 Hz: 30 fps (2560 × 1440, 1920 × 1080, 1280 × 960, 1280 × 720)
Sub-Stream	60 Hz: 30 fps (704 × 480, 640 × 480, 352 × 240)
Third Stream	60 Hz: 30 fps (1920 × 1080, 1280 × 960, 1280 × 720, 704 × 480, 640 × 480, 352 × 240)
Video Compression	Main stream: H.264 / H.264+ / H.265 / H.265+ Sub-stream: MJPEG / H.264 / H.265 Third stream: MJPEG / H.264 / H.265
H.264 Type	Baseline Profile / Main Profile / High Profile
H.265 Type	Main profile
Scalable Video Coding (SVC)	H.264 and H.265 encoding
Region of Interest (ROI)	8 fixed regions for each stream
Audio	
Audio Compression	G.711 alaw / G.711 ulaw / G.722.1 / G.726 / MP2L2 / PCM / AAC-LC
Audio Bit rate	64 Kbps (G.711) / 16 Kbps (G.722.1) / 16 Kbps (G.726) / 32 to 192 Kbps (MP2L2) / 32 Kbps (PCM) / 16 to 64 Kbps (AAC-LC)
Audio Sampling Rate	AAC-LC: 16, 32, 48 kHz; MP2L2: 16, 32, 48 kHz; PCM: 8, 16, 32, 64 kHz
Environmental Noise Filtering	Yes
Network	
Protocols	IPv4/IPv6, HTTP, HTTPS, 802.1x, Qos, FTP, SMTP, UPnP, SNMP, DNS, DDNS, NTP, RTSP, RTCP, RTP, TCP/IP, UDP, IGMP, ICMP, DHCP, PPPoE, Bonjour, WebSocket, WebSockets
Simultaneous Live View	Up to 20 channels
API	Open Network Video Interface (Version 18.12), Profile S, Profile G, Profile T), ISAPI, SDK, ISUP
User / Host	Up to 32 users; 3 user levels: administrator, operator, and user
Security	Password protection, complicated password, HTTPS encryption, 802.1X authentication (EAP-TLS, EAP-LEAP, EAP-MD5), watermark, IP address filter, basic and digest authentication for HTTP / HTTPS, control timeout settings, security audit log, TLS 1.2, host authentication (MAC address)
Network Storage	NAS (NFS, SMB / CIFS), auto network replenishment (ANR)
Web Browsers	IE 10 to 11, Chrome 57+, Firefox 52+, Safari 11+
Imaging	
Image Parameters Switch	Yes
Image Settings	Saturation, brightness, contrast, sharpness, gain, and white balance adjustable by client software or web browser
Day / Night Switch	Day, Night, Auto, Schedule
Wide Dynamic Range (WDR)	120 dB
SNR	> 52 dB
Defog	Digital Defog
Image Enhancement	BLC, HLC, 3D DNR
Privacy Mask	24 programmable polygon privacy masks, mask color or mosaic configurable

Regional Focus	Yes
Regional Exposure	Yes
Interface	
Ethernet Interface	1 RJ45 10 M/100 M self-adaptive Ethernet port
On-board Storage	Built-in memory card slot supports MicroSD / SDHC / SDXC cards up to 256 GB
Audio	1 input (line in), max. input amplitude: 2-2.4 vpp, input impedance: 1 K Ω \pm 10%; 1 output (line out), line level, output impedance: 600 Ω
Alarm	2 inputs, 2 outputs
Reset	Yes
Event Types	
Basic Events	Motion detection, video tampering alarm, exception, alarm input and output
Smart Events	line crossing detection, intrusion detection, region entrance detection, region exiting detection, unattended baggage detection, object removal detection, audio exception detection
Alarm Linkage	Upload to FTP / NAS / memory card, notify surveillance center, send email, trigger alarm output, trigger recording, and PTZ actions (such as preset, patrol scan, pattern scan)
Smart Tracking	Manual tracking, auto-tracking
Deep Learning Functions	
Face Capture	Detects up to 5 faces simultaneously, Supports detecting, tracking, capturing, grading, selecting of faces in motion, then transmits the best face picture
General	
Power	12 VDC, Max. 24 W; PoE (802.3 at)
Dimensions	\varnothing 6.65 \times 6.34 in. (\varnothing 169 \times 161 mm)
Weight	Approx. 5.40 lbs (2.45 kg)
Operating Conditions	-22° to 149° F (-30° to 65° C); Humidity 90% or less (non-condensing)
General Functions	Mirror, password protection
Certifications	
Protections	IP66 (IEC 60529-2013), TVS 6000V lightning protection, surge protection and voltage transient protection

Dimensions



Accessories (Optional)

