

CMHD7352WE-28F

Platinum 5 MP Fixed Lens HD-TVI Dome Camera



Key Features

- 5 MP high performance CMOS
- 2560 × 1944 resolution
- 2.8 mm
- EXIR 2.0, smart IR, & up to 98 feet (30 meters) of IR range
- OSD menu, 3D DNR, 130 dB True WDR
- IP67, IK10 protections
- Up the coax

Specifications

Camera	
Image Sensor	5 Megapixel progressive scan CMOS
Signal System	PAL / NTSC
Frame Rate	PAL: 5 MP @ 20 fps, 4 MP @ 25 fps, 1080p @ 25 fps NTSC: 5 MP @ 20 fps, 4 MP @ 30 fps, 1080p @ 30 fps
Resolution	2560 (H) × 1944 (V)
Min. Illumination	Color: 0.003 Lux @ (F1.2, AGC on), 0 Lux with IR
Shutter Time	PAL: 1/25 to 1/50,000 sec. NTSC: 1/30 to 1/50,000 sec.
Lens	2.8, 3.6, & 6 mm fixed lens
Horizontal Field of View	98° (2.8 mm)
Lens Mount	M12
Day & Night	IR cut filter
Angle Adjustment (Bracket)	Pan: 0° to 355°, Tilt: 0° to 75°, Rotate: 0° to 355°
Synchronization	Internal synchronization
Wide Dynamic Range (WDR)	≥ 130 dB
Menu	
AGC	Yes
Day / Night Mode	Auto / Color / B & W
White Balance	Auto / Manual
BLC (Backlight Compensation)	Yes
WDR	Yes
3D DNR	Level 1 to 10
Privacy Mask	4 programmable privacy masks
Motion Detection	4 programmable areas
Language	English
Functions	Brightness, Sharpness, 3D DNR, Mirror, Smart IR
Interface	
Video Output	1 HD analog output
General	
Operating Conditions	-40° to 140° F (-40° to 60° C); humidity: 90% or less (non-condensation)
Power Supply	12 VDC ±25%
Power Consumption	Max. 6 W
Protection Levels	IP67, IK10
Materials	Metal
IR Range	Up to 98 ft (30 m)
Communication	Up the coax (TVI output)
Dimensions	∅ 4.4 × 3.2 in. (∅ 111 × 82.4 mm)
Weight	Approx. 1.09 lbs (495 g)

Dimensions

