

CMHR6322-28F Platinum 2 MP 4-in-1 Bullet Camera











Key Features

- 2 MP high performance CMOS
- 2.8 mm fixed lens
- 2D DNR
- 4-in-1 switchable video output
- IP66 protection



Specifications

Camera	
Imaging Device	1/3" Progressive CMOS
Min. Illumination	0.05 lux @ F1.2 (AGC on), 0 Lux with IR on
Video Output	BNC
Resolution	2 MP 1920 (H) × 1080 (V)
Max. Framerate	AHD / TVI / CVI: P / @ 25 fps; N / @ 30 fps CVBS: 960 H
Focal Length (Zoom Ratio)	2.8 mm
Max. Aperture Ratio	F2.0
Angular Field of View	H: 91.84°/ V: 50.04° / D: 107.73°
Min. Object Distance	1.9 ft (0.6 m)
Lens Type	Fixed lens
Menu	
IR Range	Up to 66 ft (20 m)
On Screen Display	English
Day & Night	Ext / Color / B/W
Backlight Compensation	Off / User BLC
Digital Noise Reduction	2D DNR
Gain Control	Auto
White Balance	ATW
Electronic Shutter Speed	Auto
Reverse	Mirror
Remote Control Interface	ACP (AHD Coax Protocol)
Video Transmission Distance	Up to 300 m (Cable: 5C 2V)
General	
Operating Temperature / Humidity	-22° to 122° F (-30° to 50° C); Humidity: 90% or less (non-condensation)
Ingress Protection	IP66
Input Voltage / Current	12 VDC
Power Consumption	IR on: 3.5 W; IR off: 0.5 W
Materials	Metal
Dimensions	Φ 2.80 × 5.44 in. (Φ 71.1 × 138.3 mm)
Weight	Approx 0.72 lbs (325 g)



Dimensions





