

## *4 MP Pro-X Intelligent Color Series*

# LXIP3C42NW-28MDA



### Key Features

- Resolutions up to 4 MP (2688×1520) @ 30 fps
- 1/2.7" Starlight CMOS image sensor
- Min. Illumination 0.0005 Lux @ f1.0 (Color, 30 IRE), 0 Lux with white light
- Built-in White LED, Matrix White LED up to 98 feet
- Smart encoding H.264 / H.265
- 120 dB True WDR, 3D DNR, HLC, BLC
- MD 2.0 focuses on persons & vehicles
- Smart VCA by AI algorithm
- Built-in MicroSD card slot, up to 256 GB
- Built-in Mic
- 12 VDC / POE power supply
- IP67 protection


## LXIP3C42NW-28MDA

### Specifications

Camera	
Image Sensor	1/2.7" 4 MP progressive CMOS
Min. Illumination	0.0005 Lux @ f1.0 (Color, 30 IRE), 0 Lux (White LED on)
Shutter Speed	Auto / Manual 1/3 - 1/100,000 sec.
S/N Ratio	> 56 dB
Noise Reduction	3D DNR
Wide Dynamic Range	120 dB
Day & Night Imaging	Color / B&W
Angle Adjustment	Pan: 0° - 360°, Tilt: 0° - 78°, Rotation: 0° - 360°
Lens Type	Fixed-focal 2.8 mm @ f1.0
Iris Type	Fixed
Field of View	Horizontal: 103°, Vertical: 53°, Diagonal: 122°
Close Focus Range	3.9 ft (1.2 m)
DORI	Detect: 183.7 ft (56.0 m) , Observe: 73.5 ft (22.4 m) , Recognize: 36.8 ft (11.2 m) , Identify: 18.4 ft (5.6 m)
Illuminator	2 (warm supp. LED)
Illumination Range	98.4 ft (30 m) (Warm supp. light)
Illuminator Control	Auto / Manual
Video	
Video Compression	MJPEG (only supported by sub stream), H.264, H.264H, H.264B, H.265
Smart Codec	Supported
Resolution	4 MP (2688 × 1520), 3 MP (2304 × 1296), 1080p (1920 × 1080), 1.3 MP (1280 × 960), 720p (1280 × 720), D1 (704 × 576 / 704 × 480), VGA (640 × 480), CIF (352 × 288 / 352 × 240)
Video Frame Rates	Main stream 2688 × 1520 @ (1 - 30 fps) Sub stream 704 × 576 @ (1 - 25 fps) / 704 × 480 @ (1 - 30 fps) Third stream 1280 × 720 @ (1 - 30 fps)
Video Stream	3 streams
Bit Rate Control	CBR, VBR
Video Bit Rate	H.264: 3 Kbps - 8,192 Kbps H.265: 3 Kbps - 8,192 Kbps
ROI	Supported (4 areas)
Image Rotation	0° / 90° / 180° / 270° (Supports 90° / 270° with 1920 × 1080 resolution or lower)
Mirror	Supported
Privacy Mask	Supported (4 areas)
Audio	
Built-in Mic	Yes
Audio Compression	G.711 a, G.711 Mu, G726
Intelligent Analysis	
VCA's	Tripwire, intrusion (Supports classification and accurate detection of vehicles and persons)
MD 2.0	Yes, supports alarm triggered by vehicles and persons
Event Types	
Alarm Events	No SD card, SD card full, SD card error, less service time of SD card (smart card supports), network disconnection, IP conflict, illegal access, voltage detection, security exception, motion detection, video tampering, scene changing, intensity change, tripwire, intrusion, IMD
Network	

Protocol	IPv4, IPv6, HTTP, HTTPS, TCP, UDP, ARP, RTP, RTSP, RTCP, RTMP, SMTP, FTP, SFTP, DHCP, DNS, DDNS, QoS, UPnP, NTP, Multicast, ICMP, IGMP, NFS, PPPoE, 802.1x, SNMP
Interoperability	ONVIF (Profile S / Profile G / Profile T), API, P2P
Storage	FTP, SFTP, MicroSD Card (supports up to 256 GB), Cloud, NAS
Web Browsers	Internet Explorer: IE8, IE9, IE11, Chrome, Firefox
Client	PRO-X, X Station
<b>Interface</b>	
Network	RJ-45 (10/100 Base-T)
<b>General</b>	
Power	12 VDC / PoE (802.3 af), < 8.5 W
Housing	Aluminum alloy body, except for trim ring
Dimensions	4.15 × Φ 4.8" (105.4 × Φ122.0 mm)
Operating Conditions	-40° to 140° F (-40° to 60° C), less than 95%
Storage Conditions	-40° to 140° F (-40° to 60° C)
Protections	IP67
Net Weight	1.2 lb 90.55 kg)
Gross Weight	1.5 lb (0.69 kg)
Certifications	FCC

### Dimensions (mm[inch])



Accessories

LXJB02 Junction Box	LXWM01 Wall Mount	LXPM01 Vertical Pole Mount	LXPM02 Horizontal Pole Mount	LXKPD01 Pendant Mount	LXCM01 Corner Mount
					

