

## Platinum Turret HD-TVI Camera 3.1MP **CMHT17T2-6**







## **Key Features:**

- 3.1MP High Definition
- 6mm Fixed Lens
- 2 Matrix IR LED up to 131ft.(40m)
- DC 12V
- OSD menu via UTC technology with Platinum TVI DVR
- IP66 weatherproof
- Must be used with HD-TVI 3.0 DVRs

## **Dimensions:**





















©2016 LT Security, Inc. | info@LTSecurityinc.com | www.LTSecurityinc.com















## Platinum Turret HD-TVI Camera 3.1MP CMHT17T2-6

CAMERA	
Image Sensor	1/3"CMOS
Signal System	NTSC/PAL
Effective Pixels	2052(H)*1536(V)
Min. Illumination	0.01 Lux, 0 Lux with IR
Lens	6mm Angle of View: 44.6°
Shutter Speed	1/30(1/25) s to 1/50,000 s
Day & Night	ICR
Synchronization	Internal
Video Frame Rate	1920x1536@18fps
HD Video Output	1 HD-TVI Output
S/N Ratio	More than 62dB
MENU	
AGC	Support
D/N Mode	Color/ BW/ SMART
White Balance	ATW/ MWB
BLC	Support
Function	DNR, Mirror, SMART IR
GENERAL	
Working Temperature	-40 ° F - 140 ° F (-40 ° C - 60 ° C)
/Humidity	Humidity 90% or less (non-condensing)
Power Supply	DC 12V
Power Consumption	Max. 5W
Weather Proof Ratings	IP66
IR Range	Up to 131ft(40m)
Dimension	3.6 "×3.3" ×2.7"(91.0×82.6 × 68.3mm)
Weight	0.8lb(350g)