

Platinum Turret HD-TVI Camera 3.1MP **CMHT17T2W-28**







Key Features:

- 3.1MP High Definition
- 2.8mm Fixed Lens
- True WDR 120dB
- 2 Matrix IR LED up to 131ft.(40m)
- DC 12V
- OSD menu via UTC technology with Platinum TVI DVR
- IP66 weatherproof
- Must be used with HD-TVI 3.0 DVRs

Dimensions:



































Platinum Turret HD-TVI Camera 3.1MP CMHT17T2W-28

CAMERA	
Image Sensor	1/3"CMOS
Signal System	NTSC/PAL
Effective Pixels	2052(H)*1536(V)
Min. Illumination	0.01 Lux, 0 Lux with IR
Lens	2.8mm Angle of View: 84°
Shutter Speed	1/30(1/25) s to 1/50,000 s
Day & Night	ICR
Synchronization	Internal
Video Frame Rate	1920x1536@18fps
HD Video Output	1 HD-TVI Output
S/N Ratio	More than 62dB
MENU	
AGC	Support
D/N Mode	Color/ BW/ SMART
White Balance	ATW/ MWB
BLC	Support
Function	True WDR, DNR, Mirror, SMART IR
GENERAL	
Working Temperature	-40 ° F - 140 ° F (-40 ° C - 60 ° C)
	-40 ° F - 140 ° F (-40 ° C - 60 ° C) Humidity 90% or less (non-condensing)
Working Temperature	
Working Temperature /Humidity Power Supply Power Consumption	Humidity 90% or less (non-condensing)
Working Temperature /Humidity Power Supply	Humidity 90% or less (non-condensing) DC 12V
Working Temperature /Humidity Power Supply Power Consumption	Humidity 90% or less (non-condensing) DC 12V Max. 5W
Working Temperature /Humidity Power Supply Power Consumption Weather Proof Ratings	Humidity 90% or less (non-condensing) DC 12V Max. 5W IP66