


Platinum HD-TVI Turret Camera 2.1MP CMHT2722W-28




Key Features:

- 2.1MP High Definition
- 1920x1080P@30fps
- 2.8mm Fixed Lens
- True 120dB WDR
- 2 Matrix IR up to 131ft(40m)
- DC 12V
- OSD Menu via UTC technology with Platinum TVI DVR
- IP66 weatherproof

Dimensions:































Platinum HD-TVI Turret Camera 2.1MP CMHT2722W-28

| CAMERA | |
|--|---|
| Image Sensor | 1/2.7"CMOS |
| Signal System | NTSC/PAL |
| Effective Pixels | 1928(H)*1088(V) |
| Min. Illumination | 0.01 Lux, 0 Lux with IR |
| Shutter Speed | 1/30(1/25) s to 1/50,000 s |
| Lens | 2.8mm Angle of View: 103° |
| Day & Night | ICR |
| Synchronization | Internal |
| Video Frame Rate | 1080p@30fps/1080p@25fps |
| HD Video Output | 1 HD-TVI Output |
| S/N Ratio | More than 62dB |
| MENU | |
| AGC | Support |
| D/N Mode | Color/ BW/ SMART |
| White Balance | ATW/ MWB |
| BLC | Support |
| Function | True WDR, DNR, Mirror, SMART IR |
| | |
| GENERAL | |
| GENERAL Working Temperature | -40 ° F - 140 ° F (-40 ° C - 60 ° C) |
| | -40 ° F - 140 ° F (-40 ° C - 60 ° C) Humidity 90% or less (non-condensing) |
| Working Temperature | |
| Working Temperature /Humidity | Humidity 90% or less (non-condensing) |
| Working Temperature /Humidity Power Supply | Humidity 90% or less (non-condensing) DC 12V |
| Working Temperature /Humidity Power Supply Power Consumption | Humidity 90% or less (non-condensing) DC 12V Max. 5W |
| Working Temperature /Humidity Power Supply Power Consumption Weather Proof Ratings | Humidity 90% or less (non-condensing) DC 12V Max. 5W IP66 |