

## VSPOE-SWxxxx POE Switches

### VSPOE-SW402



### VSPOE-SW802



### VSPOE-SW1602



### VSPOE-SW2402



## Key Features

- Multiple working modes to address your business needs: Normal, Secure and Surveillance
- Support port traffic control
- Support for secure mode, all downlink ports can communicate only with uplink ports
- Up to 820ft(250m) transmission distance on surveillance mode
- Support buffer optimization

- All metal housing, safe and reliable

## Specifications

Model	VSPOE-SW402	VSPOE-SW802	VSPOE-SW1602	VSPOE-SW2402
Ports	6×100Mbps network ports (RJ45), including 4 PoE ports	10×100Mbps network ports (RJ45), including 8 PoE ports	16×100Mbps PoE ports (RJ45)+2×1000Mbps Combo ports	24×100Mbps PoE ports (RJ45)+2×1000Mbps Combo ports
Standards	IEEE802.3,IEEE802.3u,IEEE802.3az,IEEE802.3x,IEEE802.3af,IEEE802.3at		IEEE802.3,IEEE802.3u,IEEE802.3z,IEEE802.3ab,IEEE802.3x,IEEE802.3af,IEEE802.3at,IEEE802.3az	
Switching capacity	1.2Gbps	2Gbps	7.2Gbps	8.8Gbps
Forwarding performance	0.90Mpps	1.49Mpps	5.36Mpps	6.55Mpps
Packet Buffer	768Kbit	1.625Mbit	4M bit	4Mbit
MAC	2K	4K	16K	16K
Dimensions (W×D×H)	160mm x 93mm x 32mm (6.3"×3.7"×1.3")	220mm x 150mm x 44mm(8.7"×5.9"×1.7")	440mm x 207mm x 45mm(17.3"×8.1"×1.8")	440mm x 207mm x 45mm(17.3"×8.1"×1.8")
Weight	<0.6kg	<1.22kg	<4.2kg	<4.2kg
Power supply	AC: 100-240V, 50/60Hz			
PoE	802.3at/af			
Max. PoE Power	Max capacity: 65W Max capacity for single port: 30W	Max capacity: 120W Max capacity for single port: 30W	Max capacity: 250W Max capacity for single port: 30W	Max capacity: 370W Max capacity for single port: 30W
Cooling Fans	0	0	2	2
Mean Time Between Failure (MTBF)	>50000 hours			
Operating temperature	0°C-40°C (32°F-104°F)			
Operating humidity	10%~90% (noncondensing)			
Storage humidity	5%~90% (noncondensing)			
Indicator	PWR: Steady on: AC input is normal Off: No AC input			
	PoE: Off: No PoE power supply Steady on: PoE power supply is normal Flashing: PoE power supply is abnormal			
	LINK/ACT: Off: No link Steady: Linked at 10/100Mbps Flashing: Transmitting data			
	Speed: Off: Linked at 10/100Mbps On: Linked at 1000Mbps			

Working Mode	<p>Default(Normal mode) : All ports can communicate with each other.</p> <p>EXTEND(Surveillance mode): Transmission distance up to 820ft(250 meters).</p>	<p>Default(Normal mode) : All ports can communicate with each other.</p> <p>VLAN(Secure mode): Downlink ports can communicate only with uplink ports.</p> <p>EXTEND(Surveillance mode): Transmission distance up to 820ft(250 meters).</p>
--------------	---	--