

CMIP3032 3 MegaPixel Turret IP Camera

Features

- 3 MP 1/3" CMOS Sensor
- 4mm Fixed Lens
- Matrix IR LED@ 90ft
- 1080P@30fps
- Day/Night Auto switch
- POE; DC 12V
- IP66

Specifications

Model	CMIP3032	
Camera	Image Sensor	1/3" Progressive Scan CMOS
	Min. Illumination	0.05 lux @F1.2, AGC ON, 0 lux with IR 0.14 lux @F2.0, AGC ON, 0 lux with IR
	Shutter time	1/25s ~ 1/100,000s
	Lens	4mm @F2.0 Angle of view: 45.3°
	Lens Mount	M12
	Angle Adjustment	Horizontal: 0° -360°, Vertical 0°-75°, Rotate: 0° -360°
	Day& Night	ICR
Compression Standard	Wide Dynamic Range	D-WDR
	Video Compression	H.264 / MPEG4 / MJPEG
	Bit Rate	32 Kbps ~ 16 Mbps
	Dual Stream	Yes
Image	Max. Image Resolution	2048x1536
	Frame Rate	50Hz: 25fps (1920x1080), 25fps (1280x720) 60Hz: 30fps (1920x1080), 30fps (1280x720)
	Image Settings	Saturation, brightness, contrast adjustable through client software or web browser
Network	Network Storage	NAS (iSCSI optional)
	Alarm Trigger	Motion detection, tampering alarm, network disconnect , IP address conflict, storage exception
	Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, Qos (SIP, SRTP, IPv6 optional)
	Security	User authentication, watermark
	System Compatibility	ONVIF, PSIA, CGI
	General Functions	Flickerless, heartbeat, mirror, user auth., video mask
	Mobile App	NVMS7000 for iPhone/iPad./Android
Interface	Communication Interface	1 RJ45 10M / 100M ethernet interface
General	Operating Conditions	-25 °C ~ 60 °C (-13°F ~ 140 °F) humidity 95% or less (non-condensing)
	Power Supply	12 VDC ± 10%, PoE (802.3af)
	Power Consumption	max. 7W
	Weather Proof	IP66
	IR Range	Up to 90ft (Matrix IR)
	Dimensions	5.0"(W) × 3.9" (H)
	Weight	1.48 lb(670g)



IP66

Matrix IR

Dimensions

