

LTD2716TE-M

1080P TVI DVR



Key Features

16CH HD TVI video input
16CH 1080P or 720p@ 30fps live preview
16CH 1080P@ 15fps or 720P@ 30fps recording
1080P and 720P signal auto detect
Long transmission distance over coax cable
8 CH simultaneously playback

Rear Panel



1. Audio out
2. Audio in
3. HD-TVI Video in
4. HDMI Interface
5. VGA Interface
6. LAN
7. USB
8. DC 12V
9. RS-485 Serial Interface

TD2716TE-M	
Video / Audio input	
Video compression	H.264
Video input	16ch BNC (1.0 Vp-p, 75Ω)
Audio compression	G.711u
Audio input	1-ch, RCA(2.0 Vp-p, 1 kΩ)
Two-way audio input	1-ch, RCA (2.0 Vp-p, 1 kΩ) (using the audio input)
Video / Audio output	
HDMI output	1-ch, resolution: 1920×1080 /60 Hz
VGA output	1-ch, resolution: 1920x1080,1280x1024, 1024x768, 800x600/60HZ
Audio output	1-ch, RCA
Audio bit rate	64 Kbps
Recording and Playback	
Video bit rate	1M-6Mbps
Encoding resolution	1080P: 15fps(NTSC)/12fps(PAL) 720P:30fps(NTSC)/25fps(PAL);
Decoding resolution	1080P: 15fps(NTSC)/12fps(PAL) 720P:30fps(NTSC)/25fps(PAL);
Dual-stream	Yes
Synchronous playback	8-ch
Hard disk	
SATA	2 SATA interfaces
Capacity	Up to 6TB capacity for each disk
External interface	
Network interface	1, RJ45 10M / 100M Ethernet interface
RS485	1 RS485, connect to PTZ or keyboard
USB interface	2, USB2.0
Alarm in	NO
Alarm out	NO
General	
Power supply	DV12V
Power Consumption	≤10W (without hard disk)
Working temperature	-10 °C ~ + 55 °C(14 °F - 122°F)
Working humidity	10% ~ 90%
Chassis	standard 1U chassis
Dimension	430 mm x 300 mm x 55 mm
Weight	≤ 3kg(6.6lb) (without hard disk)